

TANOS

"BLACK-CAT"



Anti Slip Mats




"BLACK-CAT" -
Panther

Anti Slip Mats "BLACK-CAT"

Safety Anti Slip Mats (BC)


Anti Slip Mats for countless uses with an extremely high slip-proof effect are required to work with a low material thickness.



Anti Slip Mats "BLACK-CAT"-Panther

Heavy-duty, safety Anti Slip Mats (BCP)

Anti Slip Mats for special use as a transit support and floor covering, consisting of highly wear-resistant fabric with a special PVC and flexible foam coating.



Possibilities of use



Trade/Industry



Transport of heavy loads



Domestic

Technical Data	"BLACK-CAT" 	"BLACK-CAT"-Panther 
Colours	Anthracite	Anthracite
Fabric	PES / PA 6.6	PES / PA 6.6
Coating	Special PVC-flexible foam	Special PVC-flexible foam
Coating	Special PVC-flexible foam	Special PVC-flexible foam
Total weight	approx. 550 g/m ²	approx. 2000 g/m ²
Material thickness	3.8 mm +/- 0.3 mm 	4.4 mm +/- 0.4 mm 
Antislip effect		
Braking effect in acc. factory standard	At least 38 N	At least 20 N
Sliding friction resistance	μ 0.70 – 1.11 Test Certificate	μ 0.94 – 1.49 Test Certificate
Tensile strength / stretch		
Max. tensile strength (DIN 53857)	680 N warp , 358 N weft	550 N warp, 1350 N weft
Max. stretch (DIN 53857)	31% warp , 30% weft	25% warp, 32% weft
Environmental friendliness	Free of azoic dyes, formaldehyde, toxic heavy metals and silicone, can be disposed of as household rubbish	Free of azoic dyes, formaldehyde, toxic heavy metals and silicone, can be disposed of as household rubbish
Temperature resistance	approx. -40 °C to +120 °C	approx. -40 °C to +120 °C
Melting temperature	approx. 250 °C	approx. 250 °C
Auto-ignition temperature	approx. 350 °C	approx. 350 °C
Cleaning	Hand and machine-washable up to 60 °C with standard mild detergent	Wipe with a damp cloth and a solvent-free cleaner. Rinse with water and allow to dry
Other features	TÜV, FLOG and TUL-LOG tested quality / resistant to acids and lyes, as well as oil, petrol and diesel / UV-resistance (in accordance with DIN 54003) / grips on both sides without adhesion to almost all materials / suits any floor / holds things in place up to a 60° angle / can be cut with scissors or knife / extremely stable, tearproof	FLOG main reports / resistant to acids and lyes, as well as oil, petrol and diesel / UV-resistance (in accordance with DIN 54003) / grips on both sides without adhesion to almost all materials / suits any floor / holds things in place up to a 60° angle / can be cut with scissors or knife / extremely stable, tearproof / closed surface, no porosity to liquids, no frost formation / Heavy-duty special flooring / suitable to hold loads up to 82,5 t/m ²
		



application



Medical industry



Car industry

Anti Slip Mats

Product overview

"BLACK-CAT"

BC

Octagonal pad



Part-no.	Description	Dimensions
763001	BC-octagonal pad	15 x 15 cm

Small mats

Part-no.	Description	Dimensions
763002	BC Handy	20 x 25 cm
763003	BC Uni	45 x 60 cm
763008	BC Work	60 x 120 cm
763007	BC Car	90 x 120 cm
763004	BC Mini	30 x 180 cm
763005	BC Midi	45 x 180 cm
763006	BC Maxi	60 x 240 cm

Rolled goods

Part-no.	Description	Length	Width
763009	BC	10 m	0,20 m
763019	BC	10 m	0,25 m
763010	BC	10 m	0,30 m
763029	BC	10 m	0,35 m
763025	BC	10 m	0,40 m
763030	BC	10 m	0,43 m
763028	BC	10 m	0,45 m
763011	BC	10 m	0,50 m
763012	BC	10 m	0,60 m
763027	BC	10 m	0,65 m
763015	BC	10 m	0,70 m
763016	BC	10 m	0,80 m
763017	BC	10 m	0,90 m
763013	BC	10 m	1,00 m
763014	BC	10 m	1,20 m
763080	BC	10 m	1,50 m
763081	BC	10 m	1,80 m
763018	BC	10 m	2,00 m
763082	BC	10 m	2,20 m
763026	BC	10 m	2,40 m

"BLACK-CAT"-Panther

BCP

Octagonal pad



Part-no.	Description	Dimensions
763031	BCP-octagonal pad	15 x 15 cm

Small mats

Part-no.	Description	Dimensions
763064	BCP	20 x 20 cm
763065	BCP	80 x 60 cm
763066	BCP	12 x 125 cm
763067	BCP	12 x 245 cm
763063	BCP	80 x 120 cm
763069	BCP	12 x 1340 cm

Rolled goods

Part-no.	Description	Length	Width
763050	BCP	4 m	0,12 m
763051	BCP	4 m	0,15 m
763052	BCP	4 m	0,20 m
763053	BCP	4 m	0,30 m
763054	BCP	4 m	0,60 m
763055	BCP	4 m	1,00 m
763056	BCP	4 m	1,20 m
763070	BCP	4 m	1,60 m
763058	BCP	8 m	0,20 m
763059	BCP	8 m	1,00 m
763060	BCP	8 m	1,20 m
763071	BCP	8 m	1,60 m

TANOS GmbH

Böttgerstraße 10
D-89231 Neu-Ulm

Fon +49(0) 731-97 07 6-0
Fax +49(0) 731-97 07 6-29

info@TANOS.de
www.TANOS.de